



WELLWAY®





XC-30C

Capacity (L): 30
Dimension W x D x H (mm): 400 x 410 x 500
Watts (W): 70
Voltage(V): 220-240/100-110
Cooling Temperature(C):4-6/7-9
Energy Consumption (kWh/24h): 0.70
Net Weight (kg):15
Cooling type: Absorption



XC-40C

Capacity (L): 40
Dimension W x D x H (mm): 400 x 430 x 560
Watts (W): 70
Voltage(V): 220-240/100-110
Cooling Temperature(C):4-6/7-9
Energy Consumption (kWh/24h): 0.75
Net Weight (kg):18
Cooling type: Absorption



XC-60C

Capacity (L): 60
Dimension W x D x H (mm): 490 x 490 x 580
Watts (W): 85
Voltage(V): 220-240/100-110
Cooling Temperature(C):4-6/7-9
Energy Consumption (kWh/24h): 0.95
Net Weight (kg):21.5
Cooling type: Absorption



XC-30J

Capacity (L): 30
 Dimension W x D x H (mm): 400 x 420 x 500
 Watts (W): 70
 Voltage(V): 220-240/50-60
 Cooling Temperature(C):5~13
 Energy Consumption (kWh/24h): 0.70
 Net Weight (kg):16
 Cooling type: Absorption



BC-40C

Capacity (L): 40
 Dimension W x D x H (mm): 400 x 430 x 560
 Watts (W): 65
 Voltage(V): 220-240/50-60
 Cooling Temperature(C):5~8~12
 Energy Consumption :A+
 Net Weight (kg):18
 Cooling type: Compressor



BC-50C

Capacity (L): 45
 Dimension W x D x H (mm): 550 x 514 x 423
 Watts (W): 65 W
 Voltage(V): 220-240/100-115 V
 Cooling Temperature(C):5~8~12
 Energy Consumption :A+(EEI)
 Net Weight (kg):25.5
 Cooling type: Compressor
 Cool Preservation System (CPS)
 100% green & Hazardous Substances Free (HS)



XC-40J

Capacity (L): 40
 Dimension W x D x H (mm): 400 x 440 x 560
 Watts (W): 70
 Voltage(V): 220-240/50-60
 Cooling Temperature(C):5~13
 Energy Consumption (kWh/24h): 0.70
 Net Weight (kg):18
 Cooling type: Absorption